

FOR IMMEDIATE RELEASE
Contact Tom Phillips at (912) 264-6496
With any questions

March 14, 2008

THE KERFKORE COMPANY NOW OFFERS TIMBERFLEX IN 1/2", 5/8", AND 3/4" THICKNESS

Kerfkore Company, a manufacturer of patented bendable substrates and panel products, now offers Timberflex in a 1/2", 5/8", and 3/4" thickness.

Timberflex is ideal for custom fabrication since it is the first and only high-quality 3/4" bendable panel with a ready to paint three-ply Italian poplar face. It allows you to laminate without the need for patching or sanding. Timberflex panels can bend to a 5" radius and are perfectly flat without dips, valleys and hard spots often found in bendable plywood. It is dimensionally sized to have the same thickness throughout which assures excellent seam hiding characteristics.

Timberflex is ideally suited for traditional, custom fabrication by first forming the panel to the desired shape, and then laminating last with the desired finishing material. Users simply form the panel to the desired shape and then laminate with the desired finishing material. It was designed so that even a novice can make curved components.

Timberflex provides a higher quality end product and offers a multitude of advantages over conventional bending methods including less labor, no veneer checking or telegraphing, and elimination of sanding, patching and laying up multiple layers of plywood. Additional benefits include never "springing back" and always "hanging true". The face of the product accepts contact adhesive and allows users to create interior and exterior radiuses with almost no waste. Timberflex is available in 4'x8' and 8'x4' panel.

For additional information, visit www.kerfkore.com or contact:
The Kerfkore Company, 2630 Sidney Lanier Drive, Brunswick, GA 31525.
Phone: 800-637-3539 or 912-264-6496.
Fax: 912-262-9763.
E-mail: info@kerfkore.com

